

COMMERCIAL 30
X-SERIES

**UNMATCHED PERFORMANCE.
MANEUVERABILITY.
COMMERCIAL DURABILITY.**



Don't let its size fool you. Our Commercial 30 mower is deceptively light and easy to maneuver. In fact, it feels and handles much like its Commercial 21 counterparts. The major difference: its 30-inch cut delivers up to a 40% increase in cutting efficiency compared to a standard 21-inch mower—without wearing out the machine or its operator.

FEATURES:

- Equipped with Kohler® CV200 Command Pro® engine.
- Heavy-duty transmission for increased performance and durability.
- 30-inch cutting width allows operators to cut 40-percent more with each pass than a 21-inch walk-behind mower.
- Ground speeds up to 3.8 mph.
- Has a large-capacity 2.5 bushel bagger, reducing the number of stops.



UPGRADED TRANSMISSION

The heavy-duty wet clutch transmission and self-tensioning belt drive are designed for minimum maintenance and maximum reliability in the most demanding commercial applications. The Commercial 30 X-Series also includes a parking brake.

INCREASED POWER

The Commercial 30 X-Series is equipped with Kohler's premier single-cylinder commercial engine - the Command Pro CV200. The increased displacement of the powerful Kohler engine gives it 30-percent more torque than competing engines to quickly power through the toughest, thickest grass.

INCREASED WHEEL TORQUE

The upgraded heavy-duty transmission takes advantage of the Kohler engine's additional power. It delivers increased wheel torque to power up hills, with easier tracking on side hills. The positive drive design couples both drive wheels for maximum traction in all conditions.

The mowers landscape professionals trust 2-to-1.*

exmark.com

*Trusted 2-to-1 over the next best-selling brand of zero-turn mowers. Based on U.S. Data study by Wiese Research Associates Inc. Market Share and Additional Equipment Study (February 2016).



COMMERCIAL 30

X-SERIES

MODEL	ENGINE	SIZE	CONTROLS	WEIGHT	DIMENSIONS (W X H X L)
ECX200CKC30000	CV200 Kohler Command Pro	30"	Self-propelled	186 lbs.	31.9" x 38.25" ¹ x 68.0" ¹

¹ With handle in medium position. Varies with 0.5" cutting selections.



POWER COMPONENTS

Engine – CV200 Command Pro engine; governed to 3,500 rpm.
Air Filter – Quad-clean air cleaner
Drive System – Self-propelled, rear-wheel gear-driven.
Transmission – Infinitely variable speed selection.
Fuel Capacity – 1 gallon (3.8-L) fuel tank.
Speed – 0.0 mph to 3.8 (6.1 kmph) mph forward.
Speed Control - Finger-tip control.

DECK

Style – Fixed-deck. Ability to rear bag, side-discharge or mulch.
Widths Available – 30" (76 cm).
Cutting Height – 1.5" (3.8 cm) to 5.0" (12.7 cm) in 0.5" (1.3 cm) increments.
Blade – 2 blades at 15.4".
Blade-Tip Speed – Approximately 18,500 fpm.

EQUIPMENT

Engine Deck – 4.6-inch-deep stamped steel with welded reinforcement.
Front Tires – 9 x 2.5, semi-pneumatic.
Drive Tires – 10 x 3.0, semi-pneumatic.
Safety Package – Blade Brake Clutch (BBC).
Bag Capacity – 2.5 bushels (20 gallons).

ACCESSORIES & OPTIONS

Mulch Kit.

WARRANTY

1-Year Commercial/Consumer, 3-Year Engine



EXMARK MANUFACTURING COMPANY INC. • 415 INDUSTRIAL ROW • BEATRICE, NE 68310 • Call 402.223.6300 • exmark.com

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligations. See your dealer for details on all of our warranties. Exmark® is a registered trademark of Exmark Mfg. Co., Inc. Exmark is purchased 2 to 1 over the next best-selling brand of zero-turn mowers based on U.S. Data study by Wiese Research Associates, Inc. Market Share and Additional Equipment Study (February 2016). ©2020 Exmark Manufacturing Company, Inc. All Rights Reserved. Printed in the U.S.A. 2020. Rev 1.