



SnowDogg CM90 Snow Plow

Buyers Part Number: CM90

Buyers Products SnowDogg CM Snow Plow is a municipal-grade plow that's weight-optimized for medium duty trucks.

- The corrosion resistant 304 stainless steel moldboard stands 31 in. high and never needs paint. A robust frame spreads impact across the blade to reduce wear on vital components. • Eight 1/4 in. laser-cut vertical steel ribs • Two reinforcing diagonal ribs • Full length 2 in. cross tube • 5/8 in. cutting edge



- SnowDogg Illuminator™ LED Headlights are brighter and longer lasting than traditional halogens. Active Defrosting Technology™ keeps the Illuminators ice-free even in the biting cold - a central heat source defrosts the entire lens evenly, preventing the streaking or banding that's common with other LED plow lights. SnowDogg HX High Intensity Halogens are also available.
- Get your plow on and off your truck in minutes with the dual foot pedal mounting system. An adjustable and removable jack stand makes it easy to line up your plow and truck regardless of terrain and vehicle mounting height. Just engage the pedals, attach the safety pins, and connect the electrical. Done.
- Six stress-optimized trip springs protect your equipment from hidden curbs and obstacles.
- From the heavy duty lift cylinder and massive sector to the fully enclosed hydraulic power unit, the SnowDogg CM is built to endure whatever winter throws at you. • Powerful 2 in. lift cylinders • Over-sized 2 in. angle cylinders • Massive 4 in. quadrant • Fully enclosed 2 HP hydraulic power unit • SAE standard cartridge valves and hefty 3/8 in. rubber hoses
- Intuitive in-cab controls are simple to use even with gloves on. The one-handed controller puts all plows functions in the palm of your hand. Other standard accessories: • Heavy duty belted rubber snow deflector • Cast shoes • Wire reinforced blade guides

Specifications

| | | | |
|------------------------|---------|---------------------------|-------|
| Angle Cylinders | 2 x 12" | Angled Blade Width | 92.0" |
| Blade Height | 31" | Blade Width | 108" |

Specifications continued:

| | | | |
|----------------------------|--|---------------------------|---|
| Cutting Edge | 5/8 x 6 " | Electrical | Headlamp Rated Replaceable Micro-ISO Relays |
| Harnesses | Separate Light and Hydraulic 4GA Power Wires | Lift Cylinder | 2 x 6" |
| Lights | Dual Halogen Bulbs | Moldboard Material | 304 Stainless Steel |
| Moldboard Thickness | 12 Ga | Mounting System | Dual Foot Pedal Quick Mount |
| Plow Shoes | Standard | Plow Type | Straight Blade |
| Ribs | 10 / 2 Diagonal | Snow Deflector | 3/8 Belted Rubber |
| Stand | Detachable Jack | Trip Springs | 6 |
| Trip Style | Full Trip | Shipping Weight | 1000 lb |