

# QUEST<sup>®</sup>

S-SERIES

**PREMIUM RESIDENTIAL RIDER.  
PROFESSIONAL-GRADE CUT QUALITY.  
SUPERIOR COMFORT AND VALUE.**



No matter the job, it's always about using the right tools to do it right. So, if you're looking for professional-grade cut quality and performance in a premium residential zero-turn rider, look no further than Exmark's Quest<sup>®</sup> mower lineup. Once in the seat, you'll experience more commercial-grade features, comfort and durability, for less.

**FEATURES:**

- Equipped with Exmark<sup>®</sup> 708 V-Twin commercial-grade engine.
- Series 2 fabricated deck with choice of 50- or 60-inch cutting widths.
- Two Hydro-Gear<sup>®</sup> hydrostatic transmissions with charge pumps.
- Ground speeds up to 7.0 mph.



**COMMERCIAL FEATURES**

Exmark's Quest is a premium entry level zero-turn mower. The proven commercial features have been adapted for consumer use including the drive tires, an Exmark 24.5-horsepower<sup>1</sup>, 708 V-Twin engine and Series 2 fabricated cutting deck.



**CUTTING SYSTEM**

Series 2 fabricated cutting decks come in a choice of 50- or 60-inch width of cut. These fabricated decks have a 4-inch deep design, formed and welded using a strong 10-gauge steel top and 12-gauge steel side skirt. A heavy-duty 7-gauge bumper adds strength and better protects the deck from impact.



**SIMPLE EASY ADJUSTMENTS**

With a single-point height adjust, it's easy to vary the Quest's cutting deck. The S-Series mower is equipped with a foot lift-assist, which eases lifting and lowering the cutting deck.

The mowers landscape professionals trust 2 to 1.\*

[exmark.com](http://exmark.com)

<sup>1</sup> The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J2723. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers may be significantly lower. \*Trusted 2-to-1 over the next best-selling brand of zero-turn mowers. Based on U.S. Data study by Wiese Research Associates Inc. Market Share and Additional Equipment Study (February 2016).



# QUEST<sup>®</sup>

## S-SERIES

MODEL	ENGINE	SIZE	DECK	WEIGHT	DIMENSIONS (W X H X L)
QZS708GEM50200	Exmark 708 V-Twin	50"	Series 2 Fabricated	652 lbs.	61.7" x 42.6" x 77.0"
QZS708GEM60200	Exmark 708 V-Twin	60"	Series 2 Fabricated	681 lbs.	75.2" x 42.6" x 77.0"



### POWER COMPONENTS

**Engine** – 708cc Exmark V-Twin, governed to 3,300 rpm.

**Air Filter** – Standard engine manufacturer's air filter.

**Drive System** – Two Hydro-Gear ZT-2800 hydrostatic transmission with charge pumps, no hoses, integrated cooling fans, remote reservoir, spin-on filter and heavy-duty components.

**Hydro Fluid** – Exmark Premium Hydro Oil.

**Speed** – Infinitely variable speed selection from 0–7.0 mph (11.3 kmph) forward. 0–3.4 mph (5.5 kmph) reverse.

**PTO Engagement** – MagStop electromagnetic 105-ft-lb. clutch.

**Fuel Capacity** – 3.0-gallon (11.0-L) single fuel tank with single fill location.

**Drive-Wheel Release** – Allows unit movement without engine running.

**Safety Package** – Operator Presence Controls (OPC) and drive system interlock.

**Deck Lift** – Standard. Hand lever lift. Foot-assist lifts the deck to maneuver around obstacles.

### DECK

**Style** – Exmark Series 2 fabricated and welded steel deck. Side discharge standard with the option to bag or mulch.

**Deck Construction** – 10-gauge top that is formed and welded, 12-gauge side skirt and 7-gauge welded bumper. 3 point suspension.

**Widths Available** – 50" (127 cm) 60" 152 (cm).

**Cutting Height** – 1.5" (3.8 cm) to 4.5" (11.4 cm) in 0.5" (1.3 cm) increments, adjustable from operator seat with standard hand lever or foot-operated assist.

**Blade Spindles** – No maintenance, sealed and non-greasable spindles. 5.50"-diameter cutter housing with 17mm- (.67") diameter spindle shaft.

**Blade-Tip Speed** – Approximately 18,500 fpm.

### EQUIPMENT

**Tractor Frame** – Unibody, riveted 10-gauge steel.

**Steering and Motion Control** – Hydraulically dampened twin levers, adjustable both fore and aft. Levers are also adjustable to 2-height positions.

**Casters** – .25" thick caster yoke arms.

**Front Caster Tires** – 13 x 6.5–6, smooth pneumatic.

**Drive Tires** – 20 x 10–10, 2-ply Turf Tech TL.

**Turning Radius** – True zero-turn.

**Parking Brake** – Lever-actuated pawl brake.

**Seat Comfort** – Commercial-grade, high-back contoured foam padded with armrests. Hinged mounting and spring suspension. Adjustment is fore and aft for operator position.

**Electrical** – 12-volt battery with 15-amp alternator.

**Standard Features** – Engine hour meter and cup holder.

**Optional Features** – Hitch and floor mat.

### ACCESSORIES & OPTIONS

2-Bag Collection System, Anti-Blowout Kit, Bag Mount Kit, Bar and Step Assist Kit, Cargo Carrier, Engine Maintenance Kit, Equipment Cover, Floor Mat, Hitch Kit, Jack and Receiver, Micro-Mulch System, Turf Striping Kit and Weight Kit.

### WARRANTY

Limited Warranty: 30-Day Commercial or 3-Year Consumer, 3-Year Engine



EXMARK MANUFACTURING COMPANY INC. • 415 INDUSTRIAL ROW • BEATRICE, NE 68310 • Call 402.223.6300 • [exmark.com](http://exmark.com)

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligations. See your dealer for details on all of our warranties. Exmark® and Quest® are registered trademarks of Exmark Mfg. Co., Inc. Exmark is purchased 2 to 1 over the next best-selling brand of zero-turn mowers based on U.S. Data study by Wiese Research Associates, Inc. Market Share and Additional Equipment Study (February 2016). ©2020 Exmark Manufacturing Company, Inc. All Rights Reserved. Printed in the U.S.A. 2020. Rev 1.