

# STARIS

E-SERIES

## MANEUVERABILITY. COMPACT DESIGN. COMMERCIAL PERFORMANCE.



Exmark® engineers reinvented the stand-on zero-turn mower from the ground up. The Staris® delivers the commercial performance, durability, ergonomics and ease of service that landscape professionals need to maximize productivity and profitability. It's impressive list of innovative features include a low center of gravity design, intuitive controls and compact foot print.

### FEATURES:

- Equipped with Kawasaki® engines.
- UltraCut™ Series 3 deck with 32- or 36-inch cutting widths.
- Dual Hydro-Gear® 10cc pumps.
- Ground speeds up to 7.5 mph.
- Platform suspension with adjustable isolators.



### SERVICEABILITY & ACCESSIBILITY

All Staris models feature a flip-up front cover, giving operators easy, tools-free access for routine maintenance and cleaning. The rear cover also lifts and locks into place, providing easy access to fill and change engine oil or hydro fluid.

### OPERATOR INTERFACE

The ergonomically designed steering system makes operating the Staris easy and the innovative Smart Controller reduces downtime with maintenance reminders and on-screen machine health diagnostics. The open platform, with a non-slip rubber mat, comfortably positions operators between the drive tires. For maximum comfort, the contoured operator support pad is height-adjustable to operator preference.

### MANEUVERABILITY

Thanks to their superior maneuverability, Exmark's stand-on mowers are ideal for smaller properties, or lawns with multiple flowerbeds or tight landscaping. Plus, the ease of stepping off the machine quickly to pick up debris, open a gate or move objects makes this stand-on idea for productivity.

The mowers landscape professionals trust 2 to 1.\*

[exmark.com](http://exmark.com)

\*Trusted 2-to-1 over the next best-selling brand of zero-turn mowers. Based on U.S. Data study by Wiese Research Associates Inc. Market Share and Additional Equipment Study (February 2016).



# STARIS E-SERIES

MODEL	ENGINE	SIZE	DECK	WEIGHT	DIMENSIONS (W X H X L)
STE600CKA32300	FS600V Kawasaki	32"	UltraCut Series 3	702 lbs.	44.9" x 47.3" x 58.1"
STE600GKA36300	FS600V Kawasaki	36"	UltraCut Series 3	725 lbs.	48.0" x 47.3" x 58.1"
STE600CKA363H1	FS600V Kawasaki	36"	UltraCut Series 3	779 lbs.	48.0" x 47.3" x 58.1"



Side Discharge

## POWER COMPONENTS

**Engine** – FS600V Kawasaki V-Twin; All engines governed to 3,600 rpm.

**Air Filter** – Standard Engine Manufacturer's air filter.

**Drive System** – Two Hydro-Gear 10cc pumps powering two Parker 12 cubic inch motors.

**Hydro Fluid** – Exmark Premium Hydro Oil.

**Speed** – Infinitely variable speed selection 0–7.5 mph (12.1 kmph) forward, 0–4.0 mph (6.4 kmph) reverse.

**PTO Engagement** – Warner 105 ft-lb clutch.

**Fuel Capacity** – 5-gallon (18.9-L), single fuel tank with single fill location.

**Drive-Wheel Release** – Allows unit movement without engine running.

**Safety Package** – Operator Presence Controls (OPC) with safety interlock system indicators.

**Deck Lift** – Manual lift with hairpin from hole to hole for position adjustment on 00 models. Single-point height-of-cut with mechanical lift-assist spring on H1 model.

## DECK

**Style** – Full-floating UltraCut™ Series 3 on 32" and 36" units. Side-discharge standard with flexible discharge chute and option to bag or mulch.

**Deck Construction** – 7-gauge top that is formed and continuously seam welded, 7-gauge side skirt.

**Widths Available** – 32" (81.3 cm) and 36" (91.4 cm).

**Cutting Height** – 1.0" (2.54 cm) to 5.0" (12.7 cm) in 0.50" (1.27 cm) increments on 00 models. 1.0" (2.54 cm) to 4.5" (12.7 cm) in 0.25" (1.27 cm) increments on H1 models.

**Blade Spindles** – No maintenance, sealed and nongreasable spindles; 7.75" diameter cutter housing with 1.75" diameter splined blade driver 1.0"-diameter spindle shaft.

**Blade-Tip Speed** – Approximately 18,500 fpm.

## EQUIPMENT

**Tractor Frame** – Welded, heavy-duty 1.5" x 3" tubular steel.

**Suspension Platform** – Adjustable operator platform suspension.

**Steering and Motion Control** – Twin levers with adjustable front reference bar to modify forward ground speed.

**Casters** – 0.38" thick caster yoke arms with sealed ball bearings.

**Front Caster Tires** – 9 x 4.50–5, smooth-tread, semi-pneumatic tires with sealed ball bearings.

**Drive Tires** – 21 x 7.00–10 Kenda tires on 32" unit; 21 x 8.50–10 Kenda drive tires on 36".

**Turning Radius** – True zero-turn.

**Parking Brake** – Lever-actuated bar brake.

**Electrical** – 12-volt sealed battery with 15-amp alternator.

**Standard Features** – Engine hour meter.

## ACCESSORIES & OPTIONS

3-Bushel Bagger, 12-Volt Power Port, Accessory Adapter Kit, Light Kit, Micro-Mulch System, Operator Controlled Discharge (Hand), Strobe Light Kit and Trash Container.

## WARRANTY

Limited Warranty: 4-Year or 750 Hours (with No Hour Limit First 2 Years), 3-Year Engine



EXMARK MANUFACTURING COMPANY INC. • 415 INDUSTRIAL ROW • BEATRICE, NE 68310 • Call 402.223.6300 • [exmark.com](http://exmark.com)

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligations. See your dealer for details on all of our warranties. Exmark® and Staris® are registered trademarks of Exmark Mfg. Co., Inc. Exmark is purchased 2 to 1 over the next best-selling brand of mowers based on U.S. Data study by Wiese Research Associates, Inc. Market Share and Additional Equipment Study (February 2016). ©2020 Exmark Manufacturing Company, Inc. All Rights Reserved. Printed in the U.S.A. 2020. Rev 1.