

# JR. SOD CUTTER – HYDRO



TRUST RYAN®

Legendary performance meets new transmission technology for more power and control. The Jr. Sod Cutter – Hydro's innovative, hydrostatic, variable-speed transmission lets you power through the cut while its heavy-duty, long-lasting, cast-iron gear case and hydraulic cooling system stand up to the toughest demands—season after season.

## 1. POWERFUL HYDROSTATIC TRANSMISSION

A specifically designed hydraulic cooling system and Hydro-Gear® BDU transmission—featuring both forward and reverse drive—turn up the power without sacrificing durability.

## 2. INTUITIVE CONTROLS

A user-friendly, color-coded interface makes it easy to adjust blade depth and angle for precise cutting—no matter the soil condition.

## 3. PNEUMATIC SWIVELING REAR WHEEL

Unlock the pneumatic rear caster wheel to easily—and tightly—maneuver around landscaping, then lock it for unmatched precision on straightways.

## 4. ULTRA-LOW VIBRATION TECHNOLOGY

A rubber isolation mount absorbs shock and machine vibration before they ever reach your hands, saving your arms from fatigue.



## OPTIONAL LASER-GLADDED BLADE (ONLY AVAILABLE ON 18" MODEL)



## EXTRA 33.3% CUTTING WIDTH (ONLY AVAILABLE ON 24" MODEL)



FOR MORE INFORMATION, VISIT [RYANTURF.COM](http://RYANTURF.COM)



## JR. SOD CUTTER – HYDRO SPECIFICATIONS

<b>HONDA® Engine Model</b>	4-Cycle Honda® GX160; recoil start; on/off switch; low-oil alert
<b>Displacement</b>	9.9 cu in. (163 cc)
<b>Fuel Capacity</b>	0.82 gal (3.1 L)
<b>Oil Capacity</b>	0.61 qt (0.58 L)
<b>BRIGGS &amp; STRATTON® Engine Model</b>	4-Cycle Vanguard™ 200 Model 12V3; recoil start; cyclonic air cleaner; integrated fuel valve; engine on/off switch
<b>Displacement</b>	12.4 cu in (203cc)
<b>Fuel Capacity</b>	0.82 gal. (3.1 L)
<b>Oil Capacity</b>	0.63 qt (0.6 L)
<b>Drive</b>	A spring-tensioned belt drives a Hydro-Gear® BDU hydrostat that transfers power through an enclosed, oil-lubricated gear and chain reduction to the drive wheels
<b>Drive Wheel</b>	(2) 8 in. (203 mm) diameter knob tread; rubber-vulcanized to cast-iron hubs
<b>Lubrication</b>	Oil splash in gear case; grease fittings elsewhere
<b>Speed</b>	Up to 352 ft/min (107 m/min)
<b>Cutting Width</b>	18 in. (457 mm) or 24 in. (610 mm)
<b>Cutting Thickness</b>	Adjustable up to 2.5 in. (64 mm)
<b>Weight</b>	18 in. Model: 380 lb (172 kg); 24 in Model: 398 lb (181 kg)
<b>Width</b>	25 in. (635 mm)
<b>Length</b>	52.5 in. (1,334 mm)
<b>Height</b>	35.5 in. (902 mm)
<b>Tires</b>	Rear: 9" x 3.50"-4 with sealed ball bearings



FOR MORE INFORMATION,  
VISIT [RYANTURF.COM](http://RYANTURF.COM)

**One Bobcat Lane | Johnson Creek, WI 53038-0469**

For more information about RYAN® products, visit your RYAN® dealer today. For the location of the dealer nearest you, call 866-469-1242 or visit [www.ryanturf.com](http://www.ryanturf.com).

©2021 Clark Equipment Co. All Rights Reserved.



**TRUST RYAN®**