

# LAWNNAIRE® TOW-BEHIND AERATOR



TRUST RYAN®

Aerate more acres efficiently with the 36" Lawnnaire Tow-Behind, ideal for sports turf, recreational fields, and other mid-sized, one-to-five acre areas. Hooking up to your tractor, this tow-behind machine quickly and effortlessly aerates one-and-a-half to two acres per hour—helping you finish jobs ahead of schedule without sacrificing quality.

## 1. VERSATILE AERATION OPTIONS

Choose from 3/4 in. or 1/2 in. thick wall coring tines, 3/4 in. thick wall spooning tines, or shallow and deep slicing knives—all made from austemper-hardened steel and built built to penetrate to a depth of four inches.

## 2. CAST-IRON TINE WHEELS WITH SINTERED BUSHINGS

Avoid productivity-killing downtime with cast-iron tine wheels that feature sintered bushings and lubrication fittings for added durability and reduced maintenance needs.

## 3. INDEPENDENTLY MOUNTED TINES

Keep moving with independently mounted tine wheels that turn while tines are in the ground—allowing you to go where you need to go while maximizing productivity—for each and every job.



## MANUAL, HYDRAULIC, AND ELECTRIC LIFT OPTIONS



## ADD EIGHT ADDITIONAL TINES



FOR MORE INFORMATION, VISIT [RYANTURF.COM](http://RYANTURF.COM)



## LAWNAIRE® TOW-BEHIND SPECIFICATIONS

<b>Frame</b>	1.5 in. (38 mm) sq x 0.1875 in. (5 mm) wall tube
<b>Hitch</b>	Clevis and pin type
<b>Aerating Wheel Axle</b>	1.25 in. (32 mm) diameter
<b>Transport Wheel Axle</b>	0.75 in. (19 mm) diameter
<b>Aerating Wheels</b>	<ul style="list-style-type: none"> <li>• Cast iron with sintered bushings</li> <li>• Pressure lubrication fitting</li> <li>• Grooved for mounting aerating tines on both sides</li> <li>• Each wheel weighs 75 lb (34 kg)</li> </ul>
<b>Tines (# of)</b>	<ul style="list-style-type: none"> <li>• 8 per wheel (48 total)</li> <li>• One set 0.75 in. (19 mm) diameter coring tines standard</li> <li>• Tines are formed from austemper-hardened alloy steel</li> <li>• Wheels can be mounted with double tines, 16 per wheel (96 total)</li> </ul>
<b>Coring Depth</b>	Up to 4 in. (102 mm)
<b>Aerating Width</b>	36 in. (914 mm)
<b>Aeration Pattern</b>	<ul style="list-style-type: none"> <li>• 6 in. x 6 in. (152 mm x 152 mm) with single tines</li> <li>• 3 in. x 3 in. (76 mm x 76 mm) with double tines</li> </ul>
<b>Holes Per Square Foot</b>	<ul style="list-style-type: none"> <li>• Up to 9 (43/m<sup>2</sup>) with single tines</li> <li>• Up to 18 (86/m<sup>2</sup>) with double tines</li> </ul>
<b>Weight</b>	500 lb (227 kg)
<b>Width</b>	46 in. (1.2 m)
<b>Length</b>	68.5 in. (1.7 m)
<b>Height</b>	31 in. (787 mm)
<b>Productivity</b>	Up to 1.5 acres/hr (0.6 ha/hr) at 4 mph (6 km/hr)
<b>Towing Speed</b>	10 mph (16 km/hr) max
<b>Transport Lift</b>	Wheels are pivotable about extended axle shaft using removable lever or 700 psi hydraulic lift
<b>Transport Tires</b>	4.10/3.50-4, 2-ply, semi-pneumatic tires with ball bearings
<b>Options*</b>	Hydraulic, electric, or manual lift
<b>Power</b>	Tractor-draw
<b>Lubrication</b>	Pressure grease fittings at tine wheels and wheels

FOR MORE INFORMATION,  
VISIT [RYANTURF.COM](http://RYANTURF.COM)

One Bobcat Lane | Johnson Creek, WI 53038-0469

For more information about RYAN® products, visit your RYAN® dealer today. For the location of the dealer nearest you, call 866-469-1242 or visit [www.ryanturf.com](http://www.ryanturf.com).

©2021 Clark Equipment Co. All Rights Reserved.



**TRUST RYAN®**