

MATAWAY® OVERSEEDER



TRUST RYAN®

Heavy-duty and built to perform, the Mataway Overseeder places seeds directly into soil slits for fast germination and unmatched seed-to-soil contact, aeration, and overseeding.

OVERSEEDER FEATURES

- 1. OVERSEED WITH CONFIDENCE**
Seed flow rate is easily controlled right from the operator's station and stops automatically when the reel is raised.
- 2. ADJUSTABLE CUTTING BLADES & SEED DEPTH GUIDE**
Adjust durable cutting blades down to a depth of 0.25" while seeding at variable rates for different grass varieties and applications.
- 3. MAXIMUM GERMINATION**
The curve-shaped discs place seeds directly into soil slits for unmatched seed-to-soil contact.



SEED DEPTH GUIDE



SIMPLE OPERATION



ULTIMATE SEED-TO-SOIL CONTACT AND MAXIMUM GERMINATION



FOR MORE INFORMATION, VISIT RYANTURF.COM

MATAWAY® OVERSEEDER SPECIFICATIONS



| | |
|--------------------------------|--|
| HONDA® Engine Model | <ul style="list-style-type: none"> • 4-cycle Honda® GX390 • Recoil start • On/off switch • Low-oil alert |
| Displacement | 23.7 cu in. (389 cc) |
| Fuel Capacity | 1.6 gal (6.1 L) |
| Oil Capacity | 1.16 qt (1.1 L) |
| Clutch | Spring-loaded belt tightener |
| Drive | <ul style="list-style-type: none"> • 4L-section V-belt to front wheels by gear box and sealed roller chain • Triple 3V-section V-belts engine to reel |
| Tires | <ul style="list-style-type: none"> • Front: (2) 4.10/3.50 x 4, 2-ply pneumatic, knob tread • Rear: (2) 4.10/3.50 x 4, 2-ply pneumatic, sawtooth tread |
| Cutting Depth | Adjustable for any desired depth to 0.25 in. (6.4 mm) |
| Seeding Blade | (10) 8-point, high carbon, heat treated blades, 2 in. (51 mm) spacing |
| Flail Blade Type | 1/8 in. (3 mm) at 1 in. (25 mm) spacing |
| Fixed Blade Type | <ul style="list-style-type: none"> • 1/32 in. (1 mm) at 1/2 in. (13 mm) spacing • 1/32 in. (1 mm) at 1 in. (25 mm) spacing • 1/16 in. (2 mm) at 1 in. (25 mm) spacing • 1/16 in. (2 mm) at 1 1/2 in. (38 mm) spacing |
| Weight: Wet | 453 lb (205 kg) w/o reel |
| Width | 35.5 in. (902 mm) |
| Length | 50 in. (1,270 mm) |
| Height | 44 in. (1,118 mm) |
| Lubrication | Oil splash in gear case, grease fittings elsewhere |
| Operating Width | 19 in. (483 mm) |
| Productivity | <ul style="list-style-type: none"> • Single Pass: 80%; 18,700 sq ft/hr • Double Pass: 80%; 9,400 sq ft/hr |

FOR MORE INFORMATION,
VISIT RYANTURF.COM

One Bobcat Lane | Johnson Creek, WI 53038-0469

For more information about RYAN® products, visit your RYAN® dealer today. For the location of the dealer nearest you, call 866-469-1242 or visit www.ryanturf.com.

©2021 Clark Equipment Co. All Rights Reserved.



TRUST RYAN®